

PS MANUAL

BCS-BATTERY CHARGERS

1.0 <u>Model</u> BCS-A2404

2.0 <u>Description</u>

24 Volt 4Amp SmartCharger Battery Charger



Durst Industries Australia Pty. Ltd. durst.com.au Phone: +61 2 9660 1755

Unit 1, 11 Packard Avenue Castle Hill NSW 2154 Australia



3.0 <u>Features</u>

- Fully Automatic, Fast and Safe.
- Overcharging Protection.
- Short Circuit Protection
- High Efficiency
- Three stage Charging indicator LED's
- Eliminates Sulphation
- Compact and Lightweight
- Leads and Battery Clamps
- Australian Electrical Standard & EMC Compliant
- Available with Optional plug to suit Mobility Scooters, wheel chairs etc

4.0 Physical and Dimensional Properties

- Each unit weighs approximately 0.5 Kg
- Width 70 mm
- Length 155 mm
- Height 48 mm
- Carton Dimensions:240 x 190 x 55
- · Colour: Red

5.0 <u>Performance</u>

- Voltage 100-240 Volt
- Frequency 47-63 Hz
- Output Current: 4 Amps
- Boost Voltage 28.8 Volts
- Float Voltage 27.4 Volts
- Wattage: 117W
- Battery size Ahr 16 Ahr 40 Ahr

6.0 <u>Uses</u>

- SmartCharger Battery Charger.
- Suitable for Automotive, Marine, Mobile Home or Caravan, Mobility Appliances, Golf Carts, Solar, Deep Cycle, UPS Standby.

7.0 <u>Documentation</u>

- Bar Code Number: 9346080001478
- Product Specification Manual PS 160
- Work Instruction Manual WI 160
- Product Costing Manual PC 160



