

PS MANUAL

SMARTWASHER®

1.0 <u>Model</u> **DSW-128**

2.0 <u>Description</u>

1 x Mobile SmartWasher® 128



Durst Industries Australia Pty. Ltd. durst.com.au Phone: +61 2 9660 1755

Unit 1, 11 Packard Avenue Castle Hill NSW 2154 Australia





PS MANUAL

3.0 **Features**

- ON/OFF control, side mounted
- Flow timer with 10 and 30 minute increments
- Flow through parts brush
- User regulated independent flow control from brush or nozzle
- Thermostat maintains fluid at 42° C (adjustable to 46° C)
- Does not damage Neoprene or Rubber gaskets and seals
- Indicators: Low Fluid level indicator (Red)

Standby/ ready indicator (Green)

Power Indicator (Green)

- Complies with Australian WHS Regulations
- Patented as a non-hazardous bio remediating parts cleaning system
- Uses warm aqueous degreasing solution called "Ozzy Juice®"
- Reduces the release of VOC's and eliminates hazardous waste.
- Helps save our environment whilst protecting the health and wellbeing of your employees.

SmartWasher Certificates and Approvals



AQMD Certified DSW-SW3 Truck Grade OzzyJuice®. DSW-SW6-8 Weapons Aviation Grade OzzyJuice®.



Authorization to Mark



Declaration of Conformity



Test Certificate in Compliance with the Device Safety Act



Test Certificate in Compliance with the Device Safety Act National Sanitation Foundation. DSW-SW3, DSW-SW6-8 OzzyJuice®



Product Safety Certificate

4.0 Physical and Dimensional Properties

- Each unit weighs approximately 45.0Kg Empty
- Approximate Shipping Weight: 65.0Kg
- Material: Blow moulded High Density polyethylene





Overall Dimensions

- Width 940 mm
- Length 1190 mm
- Height 1050 mm

Inside Sink Dimensions

- Width 680 mm
- Length 1030 mm
- Height 270 mm

Shipping Dimensions

- Width 1000 mm
- Length 1200 mm
- Height 1200 mm

5.0 <u>Performance</u>

- Pump Capacity: 93.75 Kw; 330 GPH at 1 foot; sump intake see DSW-PU20
- Electrical: 240 Volt, 50 Hz
- Heater: 1000 Watt industrial Heater –see **DSW-1403**
- Capacity: Holds 250Kg Load
- Filtration: Microbe impregnated 50 micron filters changeable and disposable without special tools or equipment. see **DSW-FL4-3PK** and **MSDS FL4**
- Cleaning Solution: OzzyJuice® see DSW-SW3 and MSDS SW3

Aqueous based surfactant cleaner.

NO Flashpoint

PH Neutral biodegradable

Non-Toxic, no caustic, non flammable, non hazardous

NO VOC's, Phosphates, formaldehyde, bio solvents or solvents.

• Microbe Treatment: Ozzy BoosterTM - see **DSW-1070** and **MSDS 1070**

Environmental- shock resistant;

Preserved for minimum 18 months shelf life.

Natural occurring, non- pathogenic microbes

6.0 Uses

• Suitable for Car/Truck dealer workshops, Panel Beaters, Bus repairers, Mining Companies, Aviation, Defence, Councils, TAFE,

7.0 <u>Documentation</u>

- Bar Code Number: 9346080000051
- Product Specification Manual PS 100
- Work Instruction Manual WI 100
- Product Costing Manual PC 100

